

SHREDDER RE



Steep and deep
+ Mountain / Deep Snow



ROTAX® ENGINE	850 E-TEC	850 E-TEC Turbo R	COLOUR	Viper Red / Black Black (spring only)
----------------------	------------------	--------------------------	---------------	--

Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	
Displacement	849 cc	
Bore	82 mm	
Stroke	80.4 mm	
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	
Minimum octane	91	
Fuel tank	36 liters	
Oil tank capacity (2-stroke)	3.4 liters	

DIMENSIONS	
Vehicle overall length*	3060 mm (3700) / 3190 mm (3900)
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	381 mm / 15 in.
Track nominal length	3705 mm / 146 in.
	3923 mm (64 mm) / 154 in. (2,5 in.)
	3912 mm (76 mm) / 154 in. (3 in.)
Track profile height	64 mm / 2.5 in.
	PowderMax 76 mm / 3.0 in.
	PowderMax X-Light (3900)

POWERTRAIN	
Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminum master cylinder

SUSPENSION	
Front suspension	LFS
Front shock	KYB PRO 40 EA-3 Kashima
Rear suspension	PPS ² -DS+
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 EA-3 R Kashima

DRY WEIGHT		
Dry weight	3700: 215 kg 3900 x 2.5: 219 kg 3900 x 3.0: 215 kg	3700: 222 kg 3900: 223 kg

FEATURES			
Frame	Radien ²	Reverse	RER
Skis	Blade DS+	Heated throttle lever	Standard
Seating	Mountain Light, 1-up	Heated grips	Standard
Handlebar	U-type aluminum with hooks, low grab handle	Gauge	4.5" digital display / 10.25" Touchscreen Display
Riser block height	120 mm	USB power outlet	Yes, in front compartment
Starter	Manual with SHOT	LinQ attachment	2 pairs

*vehicle overall length without snowflap.

