

59 YETI

2019



ROTAX® ENGINE

600 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	7
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1-up
Handlebar	U-type steel with hooks, mountain strap
Riser block height	130 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)
Heated throttle lever	Standard

COLOUR



Red/Black

DIMENSIONS

Vehicle overall length	3250 mm
Vehicle overall width	1085 mm
Vehicle overall height	1420 mm
Ski stance	900 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	32 mm

SUSPENSION

Front suspension	LTS
Front shock	MC
Rear suspension	PPS-5900-A
Center shock	HPG 25
Rear shock	HPG 25

Heated grips	Standard
Gauge	Analog with display
Mirrors	Accessory
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	-
12V power outlet	Front