

ROTAX® ENGINE **600 ACE**

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	38 liters

DIMENSIONS

Vehicle overall length	2970 mm
Vehicle overall width	1265 mm
Vehicle overall height	1470 mm
Ski stance	1080 mm
Track nominal width	406 mm
Track nominal length	3487 mm
Track profile height	34 mm Cobra

Red/Black

POWERTRAIN

2011

Drive clutch type	eDrive
Driven clutch type	QRS SS
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS²-3500
Center shock	HPG 25
Rear shock	HPG 25

FEATURES

Frame	RFX ²
rraille	KEX ²
Skis	Blade XC
Seating	2-up
Handlebar	Straight steel with hooks
Riser block height	130 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	Analog with display
Mirrors	Accessory
Windshield	635 mm
Hitch	Accessory
Visor Plug front / rear	-
12V power outlet	-



