

ROTAX° ENGINE	600 E-TEC	900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc	899.0 cc
Bore	72 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	40 liters	40 liters
Oil tank capacity (2-stroke)	2,9 liters	-

COLOURBlack/Race Orange

DIMENSIONS Vahigle everall length

Vehicle overall length	3260 mm	
Vehicle overall width	1180 mm	
Vehicle overall height	1445 mm	
Ski stance	996 +/- 21 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	44 mm	

POWERTRAIN

Drive clutch type	TRA 3	eDrive II
Driven clutch type	QRS SS	
Small sprocket number of teeth	1st gear = 3.23:1 ratio	
Large sprocket number of teeth	2nd gear = 1.98:1 ratio	
Drive sprocket	-	7
Brake system	,	n braided steel brake naster cylinder

SUSPENSION

A-LFS+ with bended lower A-Arms	
HPG 36	
EasyRide	
HPG 36	
HPG 36	

FEATURES

Frame	L-XU	
Skis	Blade XC	
Seating	Modular, 1-up heated	
Handlebar	U-type steel, mountain strap	
Riser block height	130 mm	
Starter	Electric	
Reverse	Mechanical (2F-N-R)	
Heated throttle lever	Standard	

Standard	
Multifunction	
Accessory	
High (510 mm), one piece	
Standard	
Front	
Front	



