

ROTAX° ENGINE	<i>600 ACE</i>
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity (2-stroke)	-

COLOUR

Red/Black

DIMENSIONS

Vehicle overall length	3350 mm
Vehicle overall width	1085 mm
Vehicle overall height	1420 mm
Ski stance	900 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	32 mm

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	7
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LTS
Front shock	MC
Rear suspension	PPS-5900-A
Center shock	HPG 25
Rear shock	HPG 25

FEATURES

Frame	L-XU
Skis	Blade
Seating	Modular 1-up
Handlebar	Steel with hooks, mountain strap
Riser block height	205 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle leverStandardHeated gripsStandardGaugeAnalog with displayMirrorsAccessoryWindshieldHigh (510 mm), one pieceHitchStandard



©2016 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™ ® and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.