

NOTAL LIVOTIVE	000 L-1L0
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc

Bore 72 mm

Stroke 73 mm

Maximum engine speed 8100 RPM

Carburation Electronic Direct Injection

Recommended fuel type Premium unleaded

Minimum octane 95

40 liters 2,9 liters

DIN/IENIQIONIQ

DIIVILIADIDIAD	
Vehicle overall length	3500 mm
Vehicle overall width	1120 mm
Vehicle overall height	1420 mm
Ski stance	900 mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

POWERTRAIN

Oil tank capacity (2-stroke)

Fuel tank

Drive clutch type	TRA 3
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

LTS
MC
PPS-6900-A
HPG 25
HPG 36

FEATURES

Frame	L-XU
Skis	Blade with liners
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Manual, Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Analog with display
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard



