

HOW LITOURE	333 2 123
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm

850 E-TEC

Premium unleaded

Stroke 80.4 mm 7900 RPM Maximum engine speed

Electronic Direct Injection with additional Carburation booster injectors

Minimum octane 95 Fuel tank 37 liters

Oil tank capacity (2-stroke) 3,4 liters

POWERTRAIN

Recommended fuel type

POTAX® FNGINE

21118

Drive clutch type	pDrive with clicker
Driven clutch type	QRS
Small sprocket number of teeth	21
Large sprocket number of teeth	45
Drive sprocket	6
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

COLOUR



DIMENSIONS

Vehicle overall length	3230 mm
Vehicle overall width	1180 mm
Vehicle overall height	1340 mm
Ski stance	996 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	64 mm PowderMax FlexEdge

SUSPENSION

Front suspension	LFS
Front shock	KYB 40 HLCR
Rear suspension	PPS²-3700
Center shock	KYB 46 HLCR
Rear shock	KYB 46 HLCR

FEATURES

Frame	Radien
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type aluminium with hooks, mountain strap
Riser block height	165 mm
Starter	Manual, Flectric (BYR Opt.)

Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard
Gauge	Compact digital
Mirrors	Accessory
Windshield	-
Hitch	Accessory



