2018

#### Liquid-cooled, Liquid-cooled, four-stroke D.O.H.C., Engine details 3-D R.A.V.E.™ dry sump Cylinders 2 3 Displacement 594.4 cc 899.0 cc Bore 72 mm 74 mm Stroke 73 mm 69.7 mm 8100 RPM 7250 RPM Maximum engine speed Electronic Direct EFI Carburation Injection Recommended fuel type Premium unleaded Regular unleaded Minimum octane 95 95 Fuel tank 40 liters 2,9 liters (600 E-TEC) Oil tank capacity (2-stroke)

600 E-TEC

*900 ACE* 

### POWERTRAIN

ROTAX° ENGINE

Drive clutch type	TRA 3	eDrive II
Driven clutch type	QRS SS	
Small sprocket number of teeth	1st gear = 3.23:1 ratio	
Large sprocket number of teeth	2nd gear =	1.98:1 ratio
Drive sprocket	7	7
Brake system	Hydraulic brake with line, plastic m	n braided steel brake naster cylinder

## **FEATURES**

Frame	L-XU	
Skis	Blade XC	
Seating	Modular, 1-up heated	
Handlebar	Steel with hooks,mountain strap	
Riser block height	205 mm	
Starter	Electric	
Reverse	Mechanical (2F-N-R)	

©2016 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, © and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.



Commander 600 E-TEC

COLOUR	Black/Race Orange

## DIMENSIONS

Vehicle overall length	3370 mm	
Vehicle overall width	1180 mm	
Vehicle overall height	1445 mm	
Ski stance	996 +/- 21 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	44 mm	

# SUSPENSION

Front suspension	A-LFS+ with bended lower A-Arms	
Front shock	HPG 36	
Rear suspension	PPS-5900-A	
Center shock	HPG 36	
Rear shock	HPG 36	

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	Multifunction	
Mirrors	Accessory	
Windshield	High (510 mm), one piece	
Hitch	Standard	

