

# RAVE RE 600 E-TEC

## 2018



### ROTAX® ENGINE

#### 600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

### POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	25
Large sprocket number of teeth	45
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

### FEATURES

Frame	REX²
Skis	Blade XC
Seating	BD, 1-up
Handlebar	Straight aluminium with hooks
Riser block height	115 mm
Starter	Manual, Electric (Accessory)
Reverse	RER

### COLOUR



Red/Black

### DIMENSIONS

Vehicle overall length	3015 mm
Vehicle overall width	1265 mm
Vehicle overall height	1210 mm
Ski stance	1080 mm
Track nominal width	381 mm
Track nominal length	3269 mm
Track profile height	41 mm Cobra

### SUSPENSION

Front suspension	A-LFS+
Front shock	KYB 40 HLCR
Rear suspension	PPS²-3300
Center shock	KYB 46 HLCR
Rear shock	KYB 46 HLCR

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Accessory
Windshield	S / 235 mm
Hitch	Accessory