

ROTAX° ENGINE	600 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

0020011	
DIMENSIONS	
DIIVIEIVƏIUIVƏ	
Vehicle overall length	3015 mm
Vehicle overall width	1265 mm
Vehicle overall height	1210 mm
Ski stance	1080 mm
Track nominal width	381 mm

Red/Black

3269 mm

41 mm Cobra

POWERTRAINDrive clutch type

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	25
Large sprocket number of teeth	45
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Track nominal length

Track profile height

COLOUR

Front suspension	A-LFS+
Front shock	KYB 40 HLCR
Rear suspension	PPS ² -3300
Center shock	KYB 46 HLCR
Rear shock	KYB 46 HLCR

FEATURES

Frame	REX ²
Skis	Blade XC
Seating	BD, 1-up
Handlebar	Straight aluminium with hooks
Riser block height	90 mm
Starter	Manual, Electric (Accessory)
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Accessory
Windshield	S / 235 mm
Hitch	Accessory



