

# XTRIM RE 600 E-TEC

## 2018



### ROTAX® ENGINE

#### 600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

### POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	21
Large sprocket number of teeth	45
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

### FEATURES

Frame	REX²
Skis	Blade DS
Seating	1-up
Handlebar	Straight aluminium with hooks
Riser block height	130 mm
Starter	Manual, Electric (BYR opt.)
Reverse	RER

### COLOUR



Black

### DIMENSIONS

Vehicle overall length	3100 mm
Vehicle overall width	1180 mm
Vehicle overall height	1200 mm
Ski stance	996 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3487 mm
Track profile height	44 mm PowderMax

### SUSPENSION

Front suspension	A-LFS+
Front shock	KYB 40 HLCR
Rear suspension	PPS²-3500
Center shock	KYB 46 HLCR
Rear shock	KYB 46 HLCR