

HOW LITTIE	333 - 1-5
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm

850 E-TEC

 Stroke
 80.4 mm

 Maximum engine speed
 7900 RPM

 Conhumntion
 Electronic Direct Injection with additional

Carburation Electronic bliest injection will add booster injections

Recommended fuel type Premium unleaded

Minimum octane 95

Fuel tank 37 liters
Oil tank capacity (2-stroke) 3,4 liters

POWERTRAIN

RNTAX" FNGINF

Drive clutch type	pDrive
Driven clutch type	QRS
Small sprocket number of teeth	21
Large sprocket number of teeth	45
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

COLOUR

Black/Titanium

DIMENSIONS

3130 mm
1180 mm
1290 mm
996 +/- 21 mm
406 mm
3487 mm
9 mm PowderMax

SUSPENSION

Front suspension	LFS
Front shock	KYB 40 HLCR
Rear suspension	PPS ² -3500
Center shock	KYB 46 HLCR
Rear shock	KYB 46 HLCR

FEATURES

Frame	Radien
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	120 mm
Starter	Manual, Electric (BYR opt.)
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Accessory
Windshield	S / 235 mm
Hitch	Accessory



