

XTRIM SC

2018



Xtrim SC 600 E-TEC

ROTAX® ENGINE

	600 E-TEC	900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc	899.0 cc
Bore	72 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	38 liters	
Oil tank capacity (2-stroke)	3,5 liters	

POWERTRAIN

Drive clutch type	TRA 3	eDrive II
Driven clutch type	QRS	QRS SS
Small sprocket number of teeth	23	24
Large sprocket number of teeth	45	49
Drive sprocket	8	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

FEATURES

Frame	REX ²
Skis	Blade DS
Seating	1-up
Handlebar	Straight steel with hooks
Riser block height	160 mm
Starter	Electric (600 ACE) Electric, Manual (600 E-TEC)

COLOUR



DIMENSIONS

Vehicle overall length	3270 mm
Vehicle overall width	1180 mm
Vehicle overall height	1320 mm
Ski stance	996 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	39 mm DSG

SUSPENSION

Front suspension	A-LFS+
Front shock	KYB 36R
Rear suspension	PPS ² -3700
Center shock	KYB 36
Rear shock	KYB 46

Reverse	RER (600 E-TEC) Mechanical (900 ACE)
Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Accessory
Windshield	L / 410 mm
Hitch	Standard