



Bright White / Evo Red

Black

ROTAX® ENGINE	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	
Displacement	849 cc	
Bore	82 mm	
Stroke	80.4 mm	
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	
Minimum octane	91	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

DIMENSIONS	
DIFICIONS	
Vehicle overall length*	3060 mm (3700) 3190 mm (3900)
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	381 mm
Track nominal length	3705 mm 3923 mm (64 mm) 3912 mm (76 mm)
Track profile height	64 mm PowderMax 76 mm PowderMax X-Light (only 3900)

COLOUR

SUSPENSION

Oli tank capacity (2-stroke)	3.4 11	ters
POWERTRAIN		
Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system DRY WEIGHT	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder	
DRT WEIGHT	7700 015	
Dry weight	3700: 215 kg 3900 x 2.5: 217 kg 3900 x 3.0: 218 kg	3700: 221 kg 3900: 224 kg
EFATURES	-	

Front suspension	LFS
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	PPS ² -DS+
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 HLCR Kashima

FEATURES

Frame	Radien²	
Skis	Blade DS+	
Seating	Shredder DS, 1-up	
Handlebar	U-type aluminium with hooks, low grab handle	
Riser block height	145 mm	
Starter	Manual with SHOT	
Reverse	RER	

Heated throttle lever	Standard	
Heated grips	Standard 4.5 in. digital display 10.25 in. Color Display Yes, in front compartment	
Gauge		
USB power outlet		
LinQ attachment	2 pairs	



^{*}Overall vehicle length without snow flap.