

ROTAX® ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

Full Moon Silver/Orange/Black
3490 mm
1200 mm
1490 mm
996 mm
406 mm
4141 mm
39 mm DSG Flex

## **POWERTRAIN**

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## **SUSPENSION**

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide with adjustment
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien-X
Skis	Blade DS+
Seating	2-up
Handlebar	U-type steel with hooks, low grab handle
Riser block height	140 mm
Starter	Electric
Reverse	Mechanical

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2-in. wide digital display
Mirrors	Standard
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Yes, in front compartment



<sup>\*</sup> Vehicle overall length without snowflap.