

ROTAX® ENGINE	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3	3
Displacement	899.0 cc	899.0 cc
Bore	74 mm	74 mm
Stroke	69.7 mm	69.7 mm
Maximum engine speed	7250 RPM	7750 RPM
Carburation	EFI	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	42 liters	42 liters

Viper Red/Grey	
3240 mm	
1280 mm	
1540 mm	
1080 mm	
500 mm	
3923 mm	
38 mm Cobra (studded)	

POWERTRAIN

pDrive
QRS
Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 R
Rear suspension	EasyRide with adjustment
Center shock	KYB 46 Kashima
Rear shock	KYB 46 Kashima

FEATURES

,		
Frame	Radien-X	
Skis	Blade DS+	
Seating	Luxury Modular 1+1 with heating	
Handlebar	Steel with hooks	
Riser block height	Adjustable 125-165 mm	
Starter	Electric	
Reverse	Electromechanical	
Heated throttle lever	Standard	

Heated grips	Standard	
Gauge	7.2-in. wide digital display	
Mirrors	Standard	
Windshield	Extra high with side deflectors	
Hitch	Standard	
Visor Plug front / rear	Front/Rear	
12V power outlet	Front	



^{*} Vehicle overall length without snowflap.