

ROTAX® ENGINE	600 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

Orange/Full Moon Silver/Black
3400 mm
1200 mm
1540 mm
996 mm
406 mm
3923 mm
39 mm DSG

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	2-up light
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	2 pairs



 $^{^{\}ast}$ Vehicle overall length without snowflap.