



ROTAX® ENGINE	850 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3,4 liters

COLOUR	Clazier Cyan/Viper Red Black (Spring Only)
DIMENSIONS	

DIMENSIONS	
Vehicle overall length*	3120 mm
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	64 mm PowderMax FlexEdge

### **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder with protector

### **SUSPENSION**

Front suspension	LFS
Front shock	KYB 36 CR Kashima
Rear suspension	PPS <sup>2</sup> -3700
Center shock	KYB 46 HLCR Kashima
Rear shock	KYB 46 HLCR Kashima

### **FEATURES**

Frame	Radien DS
Skis	Blade DS+
Seating	BoonDocker, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Manual with SHOT

Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5-in. digital display
12V power outlet	Yes, in front compartment
LinQ attachment	1 pair



<sup>\*</sup> Vehicle overall length without snowflap.





ROTAX® ENGINE	850 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3,4 liters

COLOUR	Clazier Cyan/Viper Red Black (Spring Only)
DIMENSIONS	
Vehicle overall length*	3250 mm
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	400 mm
Track nominal length	3912 mm
Track profile height	64 mm PowderMax Light FlexEdge 76 mm PowderMax Light FlexEdge (spring only)

Clazier Cyan/Viper Red

### **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder with protector

# **SUSPENSION**

Front suspension	LFS
Front shock	KYB 36 CR Kashima
Rear suspension	PPS <sup>2</sup> -3900
Center shock	KYB 46 HLCR Kashima
Rear shock	KYB 46 HLCR Kashima

# **FEATURES**

Frame	Radien DS
Skis	Blade DS+
Seating	BoonDocker, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Manual with SHOT

RER
Standard
Standard
4.5-in. digital display
Yes, in front compartment
2 pairs



<sup>\*</sup> Vehicle overall length without snowflap.