



2022

COMMANDER



ROTAX® ENGINE

600R E-TEC

900 ACE

900 ACE
Turbo

Engine details

Liquid-cooled,
3-D R.A.V.E.™Liquid-cooled,
four-stroke
D.O.H.C.Liquid-cooled,
four-stroke
D.O.H.C.,
turbocharged

Cylinders

2

3

3

Displacement

599.4 cc

899.0 cc

899.0 cc

Bore

72,3 mm

74 mm

74 mm

Stroke

73 mm

69.7 mm

69.7 mm

Maximum engine speed

8100 RPM

7250 RPM

7750 RPM

Carburation

Electronic Direct
Injection

EFI

EFI

Recommended fuel type

Unleaded

Minimum octane

95

Fuel tank

42 liters

Oil tank capacity (2-stroke)

3,4 liters

-

-

POWERTRAIN

Gearbox

2F/N/R with push-button reverse

Drive clutch type

pDrive with clickers (600R E-TEC)
pDrive with slider shoes (900 ACE)
pDrive (900 ACE Turbo)

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
plastic master cylinder

FEATURES

Frame

Radien-X

Skis

Blade DS+

Seating

Modular, 1-up

Handlebar

U-type steel with hooks, low grab
handle

Riser block height

140 mm

Starter

Electric

Reverse

RER (600R E-TEC)
Electromechanical (ACE)

Heated throttle lever

Standard

Heated grips

Standard

Gauge

4.5-in. digital display

Windshield

Extra high with side deflectors

Hitch

Standard

Visor Plug front / rear

Front

12V power outlet

Front

Air radiator with fan

Yes

LinQ attachment

Multi-LinQ plate

COLOUR

Tactical Grey/Black

DIMENSIONS

Vehicle overall length*

3240 mm

Vehicle overall width

1200 mm

Vehicle overall height

1500 mm

Ski stance

996 mm

Track nominal width

500 mm

Track nominal length

3923 mm

Track profile height

44 mm
38 mm Cobra studded
(900 ACE & 900 ACE
Turbo)

SUSPENSION

Front suspension

LFS
with bended lower
A-Arms

Front shock

HPG 36

Rear suspension

EasyRide with
adjustment

Center shock

HPG 36

Rear shock

HPG 36

* Vehicle overall length without snowlap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved.™,* and the BRP logo are trademarks of BRP or its affiliates.

†All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

