



ROTAX® ENGINE	600 EFI	600R E-TEC
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	599.4 cc	599.4 cc
Bore	72.3 mm	72,3 mm
Stroke	73 mm	73 mm
Maximum engine speed	7500 RPM	8100 RPM
Carburation	EFI E	lectronic Direct Injection
Recommended fuel type	Unlea	ded
Minimum octane	95	
Fuel tank	37 lit	ers
Oil tank capacity (2-stroke)	3,4 lit	ers

COLOUR	Race Orange/Black	
DIMENSIONS		
Vehicle overall length*	3270 mm	
Vehicle overall width	1200 mm	
Vehicle overall height	1250 mm	
Ski stance	996 mm	
Track nominal width	406 mm	
Track nominal length	3923 mm	
Track profile height	51 mm PowderMax	

POWERTRAIN

Drive clutch type	pDrive with clickers (600R E-TEC) pDrive (600 EFI)
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS ² -DS+ -3900
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Electric and manual
Reverse	RER

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	4.5-in. digital display	
Windshield	Low	
Visor Plug front / rear	Front	
12V power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	
Ling attachment	2 pairs	



 $^{^{\}ast}$ Vehicle overall length without snowflap.





ROTAX® ENGINE	600 EFI	600R E-TEC
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	599.4 cc	599.4 cc
Bore	72.3 mm	72,3 mm
Stroke	73 mm	73 mm
Maximum engine speed	7500 RPM	8100 RPM
Carburation	EFI E	lectronic Direct Injection
Recommended fuel type	Unlea	ded
Minimum octane	95	
Fuel tank	37 lit	ers
Oil tank capacity (2-stroke)	3,4 lit	ers

COLOUR	Race Orange/Black	
DIMENSIONS		
Vehicle overall length*	3160 mm	
Vehicle overall width	1200 mm	
Vehicle overall height	1250 mm	
Ski stance	996 mm	
Track nominal width	406 mm	
Track nominal length	3705 mm	
Track profile height	51 mm PowderMax	

POWERTRAIN

Drive clutch type	pDrive with clickers (600R E-TEC) pDrive (600 EFI)
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS ² -DS+ -3700
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Electric and manual
Reverse	RER

LinQ attachment	2 pairs	
12V power outlet	Yes, in front compartment	
Visor Plug front / rear	Front	
Windshield	Low	
Gauge	4.5-in. digital display	
Heated grips	Standard	
Heated throttle lever	Standard	



^{*} Vehicle overall length without snowflap.