



ROTAX [®] ENGINE	600 ACE Liquid-cooled, four-stroke D.O.H.C.		
Engine details			
Cylinders	2		
Displacement	600 cc		
Bore	74 mm		
Stroke	69.7 mm		
Maximum engine speed	7250 RPM		
Carburation	EFI		
Recommended fuel type	Unleaded		
Minimum octane	95		
Fuel tank	37 liters		

COLOUR

Orange/Full Moon Silver/Black

DIMENSIONS

3400 mm	
1200 mm	
1540 mm	
996 mm	
406 mm	
3923 mm	
38 mm DSG	

POWERTRAIN

Drive clutch type	eDrive II		
Driven clutch type	QRS		
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder		

SUSPENSION

Front suspension	LFS with bended lower A-Arms	
Front shock	HPG 36	
Rear suspension	EasyRide	
Center shock	HPG 36	
Rear shock	HPG 36	

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	Compact digital display
Seating	2-up light	Windshield	Extra high with side deflectors
Handlebar	U-type steel with hooks, low grab handle	Hitch	Standard
		Visor Plug front / rear	Front
Riser block height	145 mm	USB power outlet	Yes, in front compartment
Starter	Electric	Air radiator with fan	Yes
Reverse	Mechanical	LinQ attachment	Multi-LinQ plate
Heated throttle lever	Standard		

* Vehicle overall length without snowflap.

©2022 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

