

XTERRAIN RE


ROTAX® ENGINE

	850 E-TEC	900 ACE Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2	3
Displacement	849 cc	899 cc
Bore	82 mm	74 mm
Stroke	80.4 mm	69.7 mm
Maximum engine speed	7,900 RPM	7,900 RPM
Carburation	Electronic Direct Injection with additional booster injectors	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	91	91
Fuel tank		37 L/9.8 gal
Oil tank capacity (2-stroke)		3.4 L/3.6 qt

POWERTRAIN

Drive clutch type	pDrive with clickers (850 E-TEC) pDrive (900 ACE Turbo R)
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

DRY WEIGHT

Dry weight	536 lb/243 kg	573 lb/260 kg
-------------------	---------------	---------------

FEATURES

Frame	Radien Radien-X	Reverse	RER (850 E-TEC) Electromechanical (ACE)
Skis	Blade XC+	Heated throttle lever	Standard
Seating	Sport, 1-up	Heated grips	Standard
Handlebar	U-type aluminum with hooks, low grab handle	Gauge	7.2 in. wide digital display
Riser block height	120 mm	Mirrors	Optional
Starter	Electric and manual Electric (Turbo)	Windshield	Low
		Visor Plug front / rear	Front
		USB power outlet	Yes, in front compartment
		LinQ attachment	2 pairs

 Platinum Silver Satin /
Viper Red

COLOR
DIMENSIONS

Overall vehicle length*	3,120 mm/122.8 in.
Overall vehicle width	1,219 mm/48 in.
Overall vehicle height	1,260 mm/49.6 in.
Ski stance	1,067 mm/42 in.
Nominal track width	406 mm/16 in.
Nominal track length	3,705 mm/146 in.
Track profile height	2 in. PowderMax

SUSPENSION

Front suspension	LFS+
Front shock	KYB 46 HLCR Kashima
Rear suspension	PPS ³ -3700
Center shock	KYB 46 HLCR Kashima
Rear shock	KYB 46 HLCR Kashima

*Overall vehicle length without snow flap.