

SHREDDER



ROTAX® ENGINE

600R E-TEC

| | |
|-------------------------------------|--|
| Engine details | Liquid-cooled, two-stroke, 3-D R.A.V.E.™ |
| Cylinders | 2 |
| Displacement | 599.4 cc |
| Bore | 72,3 mm |
| Stroke | 73 mm |
| Maximum engine speed | 8100 RPM |
| Carburation | Electronic Direct Injection |
| Recommended fuel type | Unleaded |
| Minimum octane | 95 |
| Fuel tank | 37 liters |
| Oil tank capacity (2-stroke) | 3,4 liters |

COLOUR

Viper Red / Black

DIMENSIONS

| | |
|--------------------------------|-----------------------|
| Vehicle overall length* | 3250 mm |
| Vehicle overall width | 1120 mm |
| Vehicle overall height | 1290 mm |
| Ski stance | 921 mm |
| Track nominal width | 400 mm |
| Track nominal length | 3912 mm |
| Track profile height | 64 mm PowderMax Light |

POWERTRAIN

| | |
|---------------------------|--|
| Drive clutch type | pDrive with clickers |
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

SUSPENSION

| | |
|-------------------------|-----------------------------|
| Front suspension | LFS |
| Front shock | HPG 36 |
| Rear suspension | PPS ² -DS+ -3900 |
| Center shock | HPG 36 |
| Rear shock | HPG 36 |

FEATURES

| | | | |
|---------------------------|--|------------------------------|---------------------------|
| Frame | Radien DS | Reverse | RER |
| Skis | Blade DS+ | Heated throttle lever | Standard |
| Seating | Shredder, 1-up | Heated grips | Standard |
| Handlebar | U-type aluminium with hooks, low grab handle | Gauge | Compact digital display |
| Riser block height | 145 mm | USB power outlet | Yes, in front compartment |
| Starter | Manual Electric (spring only) | LinQ attachment | 2 pairs |

* Vehicle overall length without snowflap.