

ROTAX® ENGINE	850 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

COLOUR

Dazzling Blue/Cyan Black (Spring only)

DIMENSIONS

3240 mm
1120 mm
1330 mm
921 mm
400 mm
3912 mm
76mm PowderMax Light FlexEdge 64mm PowderMax Light FlexEdge (spring only)

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 Kashima
Rear suspension	PPS ² -DS+ -3900
Center shock	KYB 36 Kashima
Rear shock	KYB 36 Kashima

FEATURES

Frame	Radien
Skis	Blade DS+
Seating	BoonDocker DS, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Manual SHOT (spring only)
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5-in. digital display
Mirrors	
Windshield	
Hitch	
Visor Plug front / rear	
12V power outlet	Yes, in front compartment

* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. [™],^{*} and the BRP logo are trademarks of BRP or its affiliates. [†]All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.





ROTAX® ENGINE	850 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

COLOUR

Dazzling Blue/Cyan

DIMENSIONS

3370 mm
1120 mm
1330 mm
921 mm
400 mm
4178 mm
76 mm PowderMax Light FlexEdge

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 Kashima
Rear suspension	PPS ² -DS+ -4100
Center shock	KYB 36 Kashima
Rear shock	KYB 36 Kashima

FEATURES

Frame	Radien
Skis	Blade DS+
Seating	BoonDocker DS, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	140 mm
Starter	Manual with SHOT
Reverse	RER
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Mirrors	
Windshield	
Hitch	
Visor Plug front / rear	
12V power outlet	Yes, in front compartment

* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. [™],^{*} and the BRP logo are trademarks of BRP or its affiliates. [†]All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

