

ROTAX® ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

3240 mm
1280 mm
1470 mm
1080 mm
500 mm
3923 mm
38 mm Cobra (studded)

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive with slider shoes
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder
	plastic master cylinder

SUSPENSION	
------------	--

Front suspension	LFS
Front shock	KYB 36
Rear suspension	EasyRide with extension lock
Center shock	KYB 36
Pear shock	KVB 36

DRY WEIGHT

Dry weight	291 kg

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical

Heated gripsStandardGauge7.2-in. wide digital displayWindshieldExtra high with side deflectorsHitchStandardVisor Plug front / rearFrontUSB power outletFront	Heated throttle lever	Standard
Windshield Extra high with side deflectors Hitch Standard Visor Plug front / rear Front	Heated grips	Standard
Hitch Standard Visor Plug front / rear Front	Gauge	7.2-in. wide digital display
Visor Plug front / rear Front	Windshield	Extra high with side deflectors
	Hitch	Standard
USB power outlet Front	Visor Plug front / rear	Front
	USB power outlet	Front
Air radiator with fan Yes	Air radiator with fan	Yes



^{*} Vehicle overall length without snowflap.