Steep ja deep





Platinum Silver Satin / Evo Red

Black (spring only)

ROTAX® ENGINE	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two- stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	
Displacement	849 cc	
Bore	82 mm	
Stroke	80.4 mm	
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

DIMENSIONS		
Vehicle overall length*	3190 mm (3900) 3335 mm (4100)	
Vehicle overall width	1055 mm	
Vehicle overall height	1280 mm	
Ski stance	863 mm	
Track nominal width	381 mm	
Track nominal length	3912 mm 4178 mm	
Track profile height	76 mm PowderMax X-Light	

POWERTRAIN

Drive clutch type	pDrive with clickers QRS Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder	
Driven clutch type		
Brake system		

DRY WEIGHT

Dry weight 3900: 207 kg 4100: 218 kg	Dry weight	3900: 207 kg	3900: 216 kg 4100: 218 kg
---	------------	--------------	------------------------------

SUSPENSION

COLOUR

Front suspension	LFS	
Front shock	KYB 36 Plus Kashima	
Rear suspension	PPS ² -DS+ (4100 spring only)	
Center shock	KYB 36 Plus Kashima	
Rear shock	KYB 36 Plus Kashima	

FEATURES

Frame	Radien²	
Skis	Blade DS+	
Seating	Shredder DS, 1-up	
Handlebar	U-type aluminium with hooks, low grab handle	
Riser block height	120 mm	
Starter	Manual with SHOT Electric (spring only on 3900)	

RER	
Standard	
Standard	
4.5-in. digital display / 10.25-in Color Display (spring only)	
Yes, in front compartment	
2 pairs	



^{*} Vehicle overall length without snowflap.