

SHREDDER RE



Steep and deep
+ Mountain / Deep Snow



Viper Red / Black
Black (only on Turbo models)

ROTAX® ENGINE

Engine details

Cylinders

Displacement

Bore

Stroke

Maximum engine speed

Carburation

Recommended fuel type

Minimum octane

Fuel tank

Oil tank capacity (2-stroke)

600R E-TEC

Liquid-cooled,
two-stroke,
3-D R.A.V.E.™

2

599.4 cc

72.3 mm

73 mm

8100 RPM

Electronic
Direct Injection

Electronic
Direct Injection

Unleaded

95

37 liters

3.4 liters

2

849 cc

82 mm

80.4 mm

7900 RPM

Electronic Direct Injection with
additional booster injectors

Unleaded

95

37 liters

3.4 liters

850 E-TEC Turbo R

Liquid-cooled,
two-stroke,
turbocharged,
3-D R.A.V.E.™

COLOUR

DIMENSIONS

Vehicle overall length*

3060 mm (3700)
3190 mm (3900)

Vehicle overall width

1120 mm

Vehicle overall height

1280 mm

Ski stance

921 mm

Track nominal width

381 mm

Track nominal length

3705 mm
3923 mm (64mm)
3912 mm (76mm)

Track profile height

64 mm PowderMax
76 mm PowderMax X-Light
(only on 3900)

POWERTRAIN

Drive clutch type

pDrive with clickers

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight

3700: 208 kg

3700: 215 kg
3900: 219 kg

3700: 222 kg
3900: 226 kg

SUSPENSION

Front suspension

LFS

Front shock

KYB PRO 40 EA-3 Kashima

Rear suspension

PPS²-DS+

Center shock

KYB 46 Plus Kashima

Rear shock

KYB PRO 46 EA-3 R Kashima

FEATURES

Frame

Radien²

Skis

Blade DS+

Seating

Mountain Light, 1-up

Handlebar

U-type aluminium with hooks,
low grab handle

Riser block height

120 mm

Starter

Manual with SHOT
Electric (only on 3700)

Reverse

RER

Heated throttle lever

Standard

Heated grips

Standard

Gauge

4.5" digital display /
10.25" Touchscreen Display

USB power outlet

Yes, in front compartment

LinQ attachment

2 pairs

* Vehicle overall length without snowflap.