

# BRUTAL RE (500 MM/20 IN)



Steep and deep  
+ Mountain / Deep Snow



● Viper Red / Black  
● Black (900 Turbo spring only)

## ROTAX® ENGINE

### Engine details

### Cylinders

### Displacement

### Bore

### Stroke

### Maximum engine speed

### Carburation

### Recommended fuel type

### Minimum octane

### Fuel tank

### Oil tank capacity (2-stroke)

## 850 E-TEC

Liquid-cooled, two-stroke, 3-D R.A.V.E.™

2

849 cc

82 mm

80.4 mm

## 900 ACE Turbo R

Liquid-cooled, four-stroke D.O.H.C., turbocharged

3

899.0 cc

74 mm

69.7 mm

7900 RPM

EFI

Unleaded

91

36 liters

3.4 liters

## POWERTRAIN

### Drive clutch type

### Driven clutch type

### Brake system

pDrive with clickers

pDrive

QRS

Hydraulic brake with braided steel brake line, aluminum master cylinder

## DRY WEIGHT

### Dry weight

259 kg

283 kg

## FEATURES

### Frame

### Skis

### Seating

### Handlebar

### Riser block height

### Starter

### Reverse

Radien-X

Blade DS+

Brutal, 1-up

U-type aluminum with hooks, low grab handle

120 mm

Electric and manual (850)  
Electric (900 Turbo)

RER (850)

Electromechanical (900 Turbo)

### Heated throttle lever

### Heated grips

### Gauge

### Windshield

### Visor plug front / rear

### USB power outlet

### Air radiator with fan

### LinQ attachment

Standard

Standard

7.2" wide digital display

Low

Front

Yes, in front compartment

Yes

Multi-LinQ plate

## COLOUR

## DIMENSIONS

### Vehicle overall length\*

### Vehicle overall width

### Vehicle overall height

### Ski stance

### Track nominal width

### Track nominal length

### Track profile height

3300 mm

1200 mm

1230 mm

996 mm

500 mm / 20 in.

3923 mm / 154 in.

60 mm / 2.35 in.  
PowderMax

## SUSPENSION

### Front suspension

### Front shock

### Rear suspension

### Center shock

### Rear shock

LFS+

KYB PRO 36 EA-3 R  
Kashima

EasyRide +

KYB 46 Plus Kashima

KYB PRO 46 EA-3 R  
Kashima

\*vehicle overall length without snowflap.