

XTERRAIN RE



+ On & Off Trail



COLOUR

ROTAX® ENGINE	850 E-TEC	Turbo R	Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, water injection system, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2		3
Displacement	849 cc		899.0 cc
Bore	82 mm		74 mm
Stroke	80.4 mm		69.7 mm
Maximum engine speed	7900 RPM		
Carburation	Electronic Direct Injection with additional booster injectors		EFI
Recommended fuel type	Unleaded		
Minimum octane	91		
Fuel tank	36 liters		
Oil tank capacity (2-stroke)	3.4 liters		

DIMENSIONS	
Vehicle overall length*	3150 mm
Vehicle overall width	1219 mm
Vehicle overall height	1260 mm
Ski stance	1067 mm
Track nominal width	406 mm / 16 in. 381 mm / 15 in. (studded)
Track nominal length	3705 mm / 146 in.
Track profile height	51 mm / 2 in. PowderMax (850 and 850 E-TEC Turbo R only) 41 mm / 1.6 in Ice Cobra (900 ACE Turbo R only)

Black (spring only on Turbo models)

POWERTRAIN			
Drive clutch type	pDrive with clickers pDrive (900 Turbo)		
Driven clutch type	QRS		
Brake system	Hydraulic brake with braided steel brake line, aluminum master cylinder		
DRY WEIGHT			
Dry weight	244 kg	253 kg	260kg

LFS+
KYB PRO 46 HLCR Kashima
PPS ³
KYB PRO 46 HLCR Kashima
KYB PRO 46 HLCR Kashima

FEATURES

Frame	Radien²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminum with hooks, low grab handle
Riser block height	120 mm
Starter	Electric and manual (850) SHOT (850 Turbo) Electric (900 Turbo)
Reverse	RER (850) Electromechanical (900 Turbo)

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	7.2" wide digital display / 10.25" Touchscreen Display	
Windshield	Low	
Visor plug front / rear	Front	
USB power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	



^{*}vehicle overall length without snowflap.