

COMMANDER

2020



ROTAX® ENGINE

	600R E-TEC	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2		3
Displacement	599.4 cc		899.0 cc
Bore	72,3 mm		74 mm
Stroke	73 mm		69.7 mm
Maximum engine speed	8100 RPM	7250 RPM	7750 RPM
Carburation	Electronic Direct Injection		EFI
Recommended fuel type	Unleaded		Unleaded
Minimum octane		95	
Fuel tank		41 liters	
Oil tank capacity	3,4 liters	-	-

POWERTRAIN

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	Radien-X
Skis	Blade XC
Seating	Modular, 1-up
Handlebar	U-type steel, mountain strap
Riser block height	140 mm
Starter	Electric
Reverse	RER (600R E-TEC) Electromechanical (ACE)
Heated throttle lever	Standard

COLOUR



Race Orange/Grey

DIMENSIONS

Vehicle overall length	3250 mm
Vehicle overall width	1180 mm
Vehicle overall height	1490 mm
Ski stance	996 +/- 21 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm

SUSPENSION

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide
Center shock	HPG 36
Rear shock	HPG 36

Heated grips	Standard
Gauge	4,5" digital
Mirrors	-
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front, Rear (as accessory)