

COMMANDER LTD 2020



ROTAX® ENGINE

600R E-TEC

900 ACE

Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	599.4 cc	899.0 cc
Bore	72,3 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	41 liters	
Oil tank capacity (2-stroke)	3,4 liters	-

COLOUR



DIMENSIONS

Vehicle overall length	3250 mm
Vehicle overall width	1180 mm
Vehicle overall height	1490 mm
Ski stance	996 +/- 21 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm

POWERTRAIN

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade XC	Gauge	7.2-in. wide digital display
Seating	Modular, 1+1	Mirrors	-
Handlebar	U-type steel, mountain strap	Windshield	Extra high with side deflectors
Riser block height	140 mm	Hitch	Standard
Starter	Electric (900 ACE) Electric, Manual (600R E-TEC)	Visor Plug front / rear	Front
Reverse	RER (600R E-TEC) Electromechanical (ACE)	12V power outlet	Front, Rear (as accessory)
Heated throttle lever	Standard		