

<i>ROTAX" ENGINE</i>	1200 4-TEC
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	1170.7 cc
Bore	91 mm
Stroke	60 mm
Maximum engine speed	7800 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tent	40 litere

Fuel tank 40 liters

POWERTRAIN eDrive II Drive clutch type QRS SS Driven clutch type 1st gear = 3.86:1 Small sprocket number of teeth Large sprocket number of teeth 2nd gear = 2.3:1Drive sprocket 8 Hydraulic brake with braided steel brake Brake system line, plastic master cylinder

COLI	NIR	
UUL	JUII	



DIMENSIONS

Vehicle overall length	3280 mm
Vehicle overall width	1290 mm
Vehicle overall height	1400 mm
Ski stance	1102 (-42) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

SUSPENSION

Front suspension	A-LFS	
Front shock	HPG 36	
Rear suspension	PPS-6900-F	
Center shock	HPG 36	
Rear shock	2 x HPG 36	

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	130 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	-
12V power outlet	Front



