

ROTAX° ENGINE	<i>900 ACE</i>
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters

Η.	LO	UR	

White/Orange

DIMENSIONS

Vehicle overall length	3280 mm
Vehicle overall width	1180 mm
Vehicle overall height	1430 mm
Ski stance	996 (+/- 21) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm

SUSPENSION

A-LFS+ with bended lower A-Arms
HPG 36
PPS-6900-A
HPG 25
HPG 36

POWERTRAIN

Small sprocket number of teeth Large sprocket number of teeth

Drive clutch type Driven clutch type

Drive sprocket

Brake system

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)
Heated throttle lever	Standard

Heated grips	Standard
Gauge	Analog with display
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front

LYNX. (

©2018 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

eDrive II

QRS SS 1st gear = 3.86:1

2nd gear = 2.3:1

7 Hydraulic brake with braided steel brake

line, plastic master cylinder