

RAVE RS 600RS E-TEC 2019



ROTAX® ENGINE

600RS E-TEC

Cylinders	2
Displacement	599.4 cc
Bore	72,3 mm
Stroke	73 mm
Maximum engine speed	8400 RPM
Carburation	Electronic Direct Injection
Recommended octane	98
Oil mixture	3 %
Fuel tank	18 liters

POWERTRAIN

Drive clutch type	Racing pDrive
Driven clutch type	Team TTS-04
Clutch engagement	5000 rpm
Secondary ratio	23/51
Brake system	Brembo Racing 4-piston

FEATURES

Frame	Radien-RS
Skis	Pilot Racing
Seating	RS

DIMENSIONS

Vehicle overall length	3170 mm
Vehicle overall width	1280 mm
Vehicle overall height	1190 mm
Ski stance	1092 mm
Track (W x L x H)	381 x 3487 x 44 mm

SUSPENSION

Front suspension	LFS Racing
Front shock	KYB 40 HLCR Kashima
Front suspension travel	260 mm
Front springs	28 N/mm
Rear suspension	PPS ² -3500-R
Shocks (Center/Rear)	KYB 46 HLCR Kashima
Springs (Center/Rear)	55/65 Nm
Rear suspension travel	390 mm

Riser block height	90 mm
Starter	Manual
Windshield	-